BELLADONNA



BELLADONNA



■ Newly developed bass-midrange driver with HECO kraft paper cone, POC dust cap (Phase Optimization Cap) and low-loss rubber surround in a sturdy die-cast aluminum basket.



■ High-quality solid metal connecting terminal with sturdy, gold-plated high-end screw terminals



■ Bass reflex configuration with flow-optimized and screwed reflex port

BELLADONNA

HIGHLIGHTS

Driver

- Newly developed tweeter with a high degree of efficiency thanks to a 30 mm silk compound dome, solid aluminum front panel with Fluktus geometry and a powerful double magnet system
- Newly developed bass-midrange driver with HECO kraft paper cone, POC dust cap (Phase Optimization Cap) and low-loss rubber surround in a sturdy die-cast aluminum basket. 32 mm diameter CCAW voice coil (Copper Coated Aluminum Wire) for optimum dynamics and detailed music reproduction
- The magnet systems of both chassis exhibit an elaborate linear design to guarantee the lowest possible distortion and optimum dynamics. Precisely calculated copper correction elements reduce THD distortion to a minimum.

Cabinet

- Elegant surfaces: Silk matt lacquer finish, side panels with a selected real wood veneer
- Extremely sturdy MDF housing with panels up to 25 mm thick
- Internal struts to stabilize the side panels and dampen resonance of the woofer
- Removable speaker grille with acoustic material and invisible magnetic mount
- Bass reflex configuration with flow-optimized and screwed reflex port

Stand


- Heavy and low-resonance construction with four sturdy aluminum struts and 36 mm thick MDF base plate
- Height-adjustable solid metal spikes with floor-friendly, damped solid metal pads

Crossover

- Elaborate, phase-optimized crossover with audiophile, tightly toleranced components
- Exclusive high-quality film capacitors in the signal path
- 18 dB/oct. slope for low and high-pass filters
- Treble level adjustment: ,linear' / ,+ 2dB'
- High-quality solid metal connecting terminal with sturdy, gold-plated high-end screw terminals, which are suitable for 4 mm banana plugs and cable lug connectors, as well as for the direct connection of cables with a cross-section of up to 10 mm²
- Bi-wiring/bi-amping option, supplied with cable bridges for single-wire operation
- High-quality internal wiring made of low-oxygen copper



BELLADONNA





■ Height-adjustable solid metal spikes with floor-friendly, damped solid metal pads



■ Heavy and low-resonance construction with four sturdy aluminum struts and 36 mm thick MDF base plate



 A secure stand as a compact loudspeaker even without a stand thanks to the unit feet included in the scope of delivery

BELLADONNA

Principle Equipment

Power Handling (RMS/Max) **Impedance Frequency Range** Frequency Response +3/-6 dB **Crossover Frequencies Recommended Amplifier Output** Sensitivity Cabinet Surface Speaker **Color Stand Dimensions Speaker (WxHxD) Dimensions Stand (WxHxD)** Weight Speaker **Weight Stand**

BellaDonna (Speaker + Stand)

2 way, bass reflex

1 x 8" mm woofer-midrange

1" dome-tweeter

150 / 250 Watts

4 - 8 Ω

28 - 52.000 Hz

34 - 38.000 Hz

2.600 Hz

30 - 250 Watts

91 dB

Iced Silver / Sunrise Cherry

Matt Aluminium / Black

276 x 450 x 462 mm

17.8 kg

17.5 kg





