

# MA240

## Professional mixing amplifier 240W



The revolutionary 19" MA240 mixing amplifier offers 240 watts in 70 or 100 volt mode and comes with 2 mic/line input and 4 stereo line, mono summed inputs.

On the rear you can find smart left-to-right 4 level priority system for audio routing, an emergency input, paging mic with chime and a 24VDC override output. The MA240 has an unseen intuitive user friendly interface and ground breaking logical rear panel. Installing or operating this amplifier is a true pleasure for every installer and end-user worldwide.

### TECHNICAL SPECIFICATIONS

19" (483 mm wide) rack mounting	yes	height- rack units (1U=44 mm) in U	2
depth (build in) in mm	290	depth (incl front) in mm	300
power supply	100 - 240 VAC	power consumption (max) in watts	320
output power RMS 100 volts in watts	240	output power RMS 4 ohms in watts	240
dynamic output power 100 volts in watts	240	minimum impedance load in ohms	4
output power tapings	70 - 100 volts - 4 ohms	zone outputs	1
MIC inputs balanced	3	inputs with Phantom power	2
line input unbalanced	4	tone control	yes
priority switch	2	VOX mute	yes
chime	yes	emergency input	1
priority output	1	priority levels	4
power amp topology	class-D	frequency response (in Hz)	60 - 20 k
cooling system	convection	applicable in 100V	yes
applicable low impedance	yes	Net weight product (kg)	6

MORE PICTURES



ACCESSORIES



**MICPAT-D**

All call dynamic paging microphone



**D-ALINP**

Active local input panel Decora style, white



**ALINP**

Active local input panel