



DMS 6410

MICROPHONE CONSOLE



Description

One type of console is available; through DIP switches you can configure it as Chairman, Delegate or Interpreter. An added value feature the RCF Forum 6000 System has an integrated single language interpretation facility; simultaneous or sequential Listening to the translated language is achieved using the headphone sockets available on each microphone set. The consoles configured as an interpreter can be one or two, linked to the dedicated RJ connectors on the main unit DMU 6100. Interpreters work using the console microphone and console sockets for headphone. Speak slowly command is available and lights-up an LED on the active microphone. When configured the 'Delegate Console' has a microphone button and mute facility, in 'Chairman Mode' the system offers talk and priority buttons that, if pushed together cancel the active microphones on the system for override purposes.

Delegate and Chairman talk buttons are smart buttons working both as PTT or PTL (push to lock) according respectively to a long or short pressure of the buttons. On the president console a chime-tone can be associated to a priority activation of the chairman priority button; the chime sound can be also activated through terminals available on the rear panel of the master unit. Audio quality is assured by a professional gooseneck hyper-cardioid microphone that, according to the version is screwed directly into the base (fixed installations) or plugged through an XLR connector (rental/portable) and a high efficiency high intelligibility full-range speaker with neodymium magnet. Volume control is adjusted by push-buttons.

Features



DMS 6410

MICROPHONE CONSOLE

Line Art 2D

- › Standard system: up to 60 consoles DMS 6410 (2 lines; 30 consoles per line connected in daisychain)
- › Expanded system: up to 180 consoles DMS 6410 (6 lines; 30 consoles per line connected in daisychain. The further 120 consoles can be added by installing the optional board DEC 6104 into the central unit DMU 6100 and connecting the external power supply unit DPS 6202
- › 2 aux inputs, A and B, with XLR sockets, each configurable by means of DIP switches (PHANTOM, MIC / LINE, HIGH-PASS) and with a gain control and an enable / mute command
- › Audio input PLAY and audio output SYSTEM for recording
- › Audio input and output for teleconference
- › Simultaneous / sequential translation (1 translated language)
- › Each console can be set to 1 of the 3 available modes: chairman (max. 3), delegate, interpreter (max. 2). Chairmen have no limits about their microphone activation and can also mute / disable all delegate consoles (and cancel their bookings). If 2 interpreters are present, only one will be allowed to speak (1 translated language only)
- › Backlit LCD and function keys to enter the software menus and edit: Operating mode (max. number of activated delegates, max. queue length of the delegates' booking, etc.) Configuration (priority level among inputs A, B and the system; VOX function on inputs A, B; etc.) Volume levels

Part Number

17180011 DMS 6410



Grey

EAN 8024530005702



DMS 6410

MICROPHONE CONSOLE



TECHNICAL SPECIFICATIONS

Microphone specifications

Type	Electret
Directivity	Cardioid
Frequency Response (-3dB)	70 Hz - 18 kHz
Signal / Noise ratio @1kHz	60.00 dB

Console specifications

Console Type	Conference
Working with	FORUM 6000
LED indicators	Yes

Power requirement

Operating voltage	48.00V ~ Hz
-------------------	-------------

Connections

Connectors	RJ45
Daisy-chain	Yes

Accessories

Cable included	Yes
Cable length (m)	2.5

Standard compliance

Safety agency	CE compliant
---------------	--------------

Physical specifications

Cabinet/Case Material	Plastic
Color	Grey

Size / Weight

Height	63 mm / 2.48 inches
Width	200 mm / 7.87 inches
Depth	135 mm / 5.31 inches
Weight	1.22 kg / 2.69 lbs

ACCESSORIES

Cables

CABLES KIT	
17180014	DCA 6000

EAN 8024530005757



DMS 6410

MICROPHONE CONSOLE

Cables	17180029	DCA 6005	EAN 8024530006242
	17180031	DCA 6020	EAN 8024530006266