

## **CM608D**

6.5" two-way, thin edge ceiling loudspeaker, white



The Apart CM608D 6.5" two-way built-in low impedance loudspeaker is very suitable for the distribution of background music. It provides a warm background sound and can be used with a standard hi-fi amplifier. This loudspeaker is easy to install, due to its handy Quick Fit connector, an in and out push terminal for loudspeaker wire connection up to 2.5 mm. The RAL paintable thin edge grille makes it easy to integrate high quality background sound with any interior. The CMD608D is the design version of our reference install built-in loudspeaker the Apart CM608.

## **TECHNICAL SPECIFICATIONS**

outside diameter in mm	210	depth in mm	75
cutout in mm	186	installation grip range in mm	2 - 25
loudspeaker system	2-way	woofer size in inch	6.5
woofer cone material	polypropylene	tweeter size in inch	1
mounting system	3 screws	colour	white
impedance in ohms	8	low impedance dynamic power	60
low impedance RMS power in 40 watts	40	in watts	
	10	SPL 1W/1m in dB	92
max SPL 1m in dB	104	frequency response in Hz	60 - 20K
main construction material	ABS plastic	grille main material	steel
IP rating		applicable low impedance	yes
applicable in 100V	no	Vertical dispersion angle 1000 Hz	180°
closest RAL colour (subject to deviations)	RAL9010		
		Net weight product in kg	1.24







