

EVID-EC6.2E Ceiling speaker 6.5" EVAC white

EVID Entry Ceiling

- Bezel-less design with easy-attach grille
- Front baffle wattage tap adjustment
- Includes tile rail and C-Ring for easy installation
- UL 1480, UL 1480A, EN54-24:2008, UL 2043, CAN/ULC 541:2023, CSA C22.2 No. 205, and IEC 62368-1 certified



The Electro-Voice EVID-EC6.2E is a complete 6.5-inch coaxial two-way loudspeaker that offers excellent sound quality and outstanding reliability with first-class aesthetics. The EVID-EC6.2E utilizes a transformer that offers a selection of 1.88 (70-V only), 3.75, 7.5, 15 or 30 watts delivered to the loudspeaker system using either 70-V or 100-V lines, or 8-ohm bypass. Selection is via a convenient switch on the front baffle. The perforated grille is finished in semi-gloss white powder-coated enamel. The baffle is constructed from UL 94V-0 rated ABS. The rear enclosure is constructed from heavy gauge coated steel. The low-profile enclosure makes it easy to mount in very tight spaces. A side terminal-cover provides access to a 4-pin terminal block that allows direct connection to the speaker with 12-gauge and 3.3 mm²-wire and provides pass through to additional speakers.

A mounting ring and a tile bridge are included for safe suspension of the EVID-EC6.2E ceiling systems in a drop ceiling that uses mineral wool, or other fiber-based ceiling tiles.

The wide range of EVID ceiling speakers has been designed to work together as a complete system in a variety of different ceiling constructions, and to be used in combination with other EVID surface-mount and in-wall speakers

Parts included

Quantity	Component
2	Ceiling loudspeaker
2	Loudspeaker connection cover (installed)
2	Magnetic grille

Quantity	Component
4	Ceiling tile rail
2	C-ring
4	Screw
1	Cutout template
2	Paint cover
1	Quick installation guide

Technical specifications

Frequency range (-10 dB) (Hz) ¹	85 Hz – 20,000 Hz
Maximum SPL (continuous) (dB) ²	107 dB
Maximum SPL (peak) (dB) ²	113 dB
Sensitivity (1 W, 1 m) ³	92 dB SPL 1 W, 1 m
Coverage angle conical (°)	110°
Power handling (continuous) (W)	30 W
Power handling (peak) (W)	120 W
Long term power handling (continuous) (W) ⁴	30 W
Long term power handling (peak) (W) ⁴	120 W
Nominal impedance (Ω)	8 Ω
Recommended high pass (Hz) ⁵	70 Hz
Transformer taps 70 V line (W)	30 W, 15 W, 7.5 W, 3.75 W, 1.88 W
Transformer taps 100 V line (W)	30 W, 15 W, 7.5 W, 3.75 W
LF transducer size (in)	6.5 in
HF transducer size (in)	1 in

Material	Steel
Grille material	Powder coated steel
Connector type	4-pin Euroblock Input + Pass through
Wire size (AWG)	12AWG (maximum)
Wire diameter (mm²)	3.3 mm² (maximum)
Color	White; Customized colors
Color (RAL)	RAL 9003 Signal white
Mounting cutout (in)	10.70 in
Mounting cutout (mm)	272 mm
Dimensions (Ø x D) (in)	12.13 in x 6.10 in
Dimensions (Ø x D) (mm)	308 mm x 153.80 mm
Mounting depth (in)	5.9 in
Mounting depth (mm)	149 mm
Ceiling thickness (in)	0.5 in - 1.5 in
Ceiling thickness (mm)	12.5 mm - 38 mm
Weight (kg) ⁶	3.60 kg
Weight (lb) ⁶	7.9 lb
Shipping weight (kg) ⁷	9.7 kg
Shipping weight (lb) ⁷	21.4 lb
IP rating	IP34
Weatherization	Indoor
Operating temperature (°F)	32 °F – 122 °F
Operating temperature (°C)	0 °C – 50 °C
Safety agency ratings	UL 1480, UL 1480A, EN54-24:2008, safe for use in air- handling spaces per UL 2043, CAN/ ULC 541:2023, CSA C22.2 No. 205 certified, IEC 62368-1

¹Half-space (in-ceiling mounted)

²Calculated

³Half-space (1 W/1 m)


⁴Continuous pink noise (100 hours) 15.5 Vrms

⁵24 dB/octave

⁶Single product

⁷Pair of products

Dimensions



Installation note

This is a professional product that should be installed, used and maintained by trained professionals only.

Ordering information

EVID-EC6.2E Ceiling speaker 6.5" EVAC white

Two-way 6.5-inch coaxial ceiling speaker, with internal up-to-30 W 70/100-volt line transformer with 8 Ohm bypass, EN54-certified, packaged in pairs, white
Order number **EVID-EC6.2E | F.01U.417.789**

