

5.25" Two-Way All-Weather Loudspeaker



AW-525

The AW-525 all-weather loudspeaker brings clean, clear, dynamic Klipsch quality performances to patios, terraces, balconies, gardens or poolsides. And because it's so efficient, you get much more sound per watt, enabling this full-range model to work well in wide-open spaces.

Featuring a 5.25-inch IMG woofer, 1-inch titanium dome tweeter mated to a square Tracrix® Horn, durable UV-resistant enclosure, non-corrosive grille, easy draining input cup, heavy gauge zinc C-bracket and a 3/8"-16 threaded insert, the AW-525 easily creates the ultimate outdoor sound experience.

Regardless of what Mother Nature throws its way, the AW-525 will continue to deliver big time sound and worry-free performances.

- High sensitivity and power handling
- Paintable UV-resistant ABS enclosure with rustproof aluminum grille
- 3/8"-16 threaded insert for optional mounts
- Supplied with C-style mounting bracket and stainless steel hardware
- 90° x 90° Tracrix Horn tweeter for clean, clear highs

SPECIFICATIONS

FREQUENCY RESPONSE	80Hz-20kHz ± 3dB
SENSITIVITY	94dB @ 1 watt/1 meter
NOMINAL IMPEDANCE	8 ohms
CROSSOVER FREQUENCY	2450Hz
POWER HANDLING	75 watts (300 watts peak)
ENCLOSURE/MATERIAL TYPE	Bass-reflex via dual front-firing ports/ABS
DRIVE COMPONENTS	Two-way system using one 1" (2.5cm) titanium dome tweeter with a 90° x 90° Tracrix Horn and one 5.25" (13.3cm) IMG woofer
WIRE GAUGE ACCOMMODATED	12
WEIGHT	6.5 lbs. (3kg)
HEIGHT	11.8" (29.8cm)
WIDTH	8" (20.3cm)
DEPTH	9" (22.9cm)
FINISH	White or Black enclosure and grille

www.klipsch.com
1-800-KLIPSCH



All specifications are subject to change without notice. ©2004