

# HS121

## Polyvalent Sound Projector

# AUDAC

### ► Features

- Full range sound projector
- Strong ABS flame retardant housing
- Rotateable power tapping connector
- Integrated steel safety cable
- Wide and smooth frequency response
- Meets the IP65 standards

### ► Applications

- Wide variation of in- and outdoor applications
- Shoppingstreets
- Factory halls
- Amusement parks
- Playgrounds



The HS121 is a full range sound projector based on a 4" driver, especially designed to provide quality sound with a long throw range in a wide variation of in- and outdoor applications.

Its wide, smooth frequency response and high efficiency ensure high-fidelity music reproduction along with superb projection of clear and intelligible speech at very low distortion.

It delivers a power of 20W RMS in standard 8 Ohm systems with a maximum power of 40 W, but it can also be used in 100V PA systems. The 100V line transformer has power tapplings for 20W, 10W and 5W which can be selected by the special designed 5-pin waterproof connector. This connector allows to select the desired power tapping depending on the angle of rotation of the connector.

The housing is made of the strongest ABS material in a light-grey colour, ensuring a smooth blend of the loudspeaker in all different kinds of environments.

The IP rating of IP65 makes it suitable for indoor as well as outdoor use.

For safety reasons is the speaker provided with an internal steel safety cable, which prevents the speaker from falling, even in situations where the housing of the speaker has been damaged or broken.

### ► Specifications

SYSTEM SPECIFICATIONS	
Max power	40 W
RMS power	20 W
Power line transformer 1	20 W / 500 Ohm
Power line transformer 2	10 W / 1000 Ohm
Power line transformer 3	5 W / 2000 Ohm
Impedance speaker	8 Ohm
Sound pressure 1W/1m	98 dB
Sound pressure Max W/1m	114 dB
Frequency response -3dB	150 Hz - 13 kHz
PRODUCT FEATURES	
Dimensions (Width x Height x Depth)	220 x 160 x 230 mm
Weight net	2.3 Kg
Drivers	4" Full range
Connectors	5-pin waterproof connector
Construction	ABS
Front finish	Aluminium grill
Mounting	Inox bracket, inox screws
Colour	Grey (RAL 7035)
SHIPPING & ORDERING	
Packaging	Carton box
Shipping weight & volume	2.4 Kg - 0. 0081Cbm
Accessory included	Mounting bracket 5-pin connection cable (30 cm)
Optional accessories	AU570120005 - 5-pin cable 0.5 m AU570120025 - 5-pin cable 2.5 m AU570120050 - 5-pin cable 5 m
*AUDAC reserves the right to change specifications without notice: this is part of our policy to continually improve our products	