

CS55

Presentation:

This CS55 is a public address speaker for ceiling applications designed for commercial audio applications taking advantage of a high quality coaxial transducer to provide quality sound results.

It features a 5" (05" TWT) high quality full range coaxial loudspeaker and an integrated 70V/100V 'matching transformer' allowing multiple CS55 to be connected together without danger of overloading the power amplifier (to avoid impedance drop).

The speaker offers power tapping, making it suitable for high impedance (70V, 100V) voltage line and low impedance (8 ohm) installations. The transformer is contained within a metal can enclosure to improve response.


Made of lightweight yet resistant ABS plastic, this speaker has a metal grille with powder coated iron mesh.

Offering a very clean design this CS55 is the perfect solution for all kind of public address installations, designed to offer an economic but professional solution to contractors, suited for audio installations as shops, shopping malls, supermarkets, medical centers, and small rooms.



Features:

- Public address installation speaker
- Ultra slim and clean design
- 5" FR transducer + 0.5" TWT
- Suitable for 70V & 100V high imp. installations
- Suitable for 8ohm low imp. installations
- Full protection of the transformer
- Easy, fast and safe fastening system
- ABS plastic housing
- Powder coated iron mesh grille



Technical specifications:

Acoustical

Type	2-way Public address ceiling speaker
Transducer type	5" FR transducer + 0.5" TWT
Power taps (100V)	20W (500 ohm) / 10W (1k ohm) / 5W (2k ohm) / 2.5W (4k ohm)
Power taps (70V)	20W (245 ohm) / 10W (490 ohm) / 5W (980 ohm) / 2.5W (1k96 ohm) / 1.25W (3k92 ohm)
Power taps (low impedance)	20 W at 8ohm
Frequency range	100Hz - 20Hz
Sensitivity	88dB
Max. SPL	101dB

Mechanical

Colour	RAL9016
Housing	ABS plastic
Grille	Powder coated iron mesh
Mounting dimensions	Ø170 x 30mm (cut out)
Dimensions	Ø203 x 145mm
Weight	1.8Kg

